




## Cable / cable termopar plano aislado tipo T PFA (IEC) - hilo de 7/0,2 mm



Legend: K (green), J (grey), T (brown), N (pink)



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

**Cable / Cable de termopar plano aislado tipo T PFA (IEC)**

Par plano aislado de tefln con PFA. El tefln PFA tiene una buena resistencia y flexibilidad mecnic, resistente a aceites, cidos y otros fluidos adversos, gases, vapor y presin.

**Especificaciones**
**Specifications**

<b>General Description</b>	Resistant to oils, acids other adverse agents and fluids. Good mechanical strength and flexibility. PTFE better for steam/elevated pressure environments.
<b>Cable Length</b>	10m, 25m, 50m, 100m, 200m
<b>Cable Type</b>	PFA insulated, laid flat with PFA jacket
<b>Core / Strands</b>	7/0.2mm
<b>Conductor Cross Section 7/0.2 (mm<sup>2</sup>)</b>	0.219
<b>Outer Colour</b>	Brown
<b>+ Colour</b>	Brown
<b>- Colour</b>	White
<b>Drain Wire</b>	No
<b>Insulation Material</b>	PFA Insulated
<b>Loop Resistance 7/0.2 (Ohms per combined metre)</b>	2.3
<b>Max. Temperature</b>	+260°C
<b>Min. Temperature</b>	-75°C



<b>+ Conductor</b>	Copper
<b>- Conductor</b>	Constantan
<b>Screen</b>	No
<b>Standards Met</b>	Colour code (cores & jacket) to IEC-584-3
<b>Thermocouple Type</b>	T
<b>Tolerance</b>	Class 1