Cable / cable termopar de doble par trenzado aislado tipo J PTFE - hilo de 1/0,2 mm







Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Datasheet

Cable / Cable de termopar tipo J de par trenzado tipo PTFE (IEC)

Doble par trenzado aislante de PTFE. El PTFE tiene una buena resistencia y flexibilidad mecnica, resistente a aceites, cidos y otros fluidos adversos.

Especificaciones

Specifications

General Description	Resistant to oils, acids adverse agents and fluids. Good mechanical strength and flexibility.
Cable Length	10m, 25m, 50m, 100m
Cable Type	Twin twisted pair for extending or making simple thermocouples
Core / Strands	1/0.2mm
Conductor Cross Section 1/0.2 (mm2)	0.032
+ Colour	Black
- Colour	White
Drain Wire	No
Insulation Material	PTFE insulated
Loop Resistance 1/0.2 (Ohms per combined metre)	19.3
Max. Temperature	+260°C
Min. Temperature	-75°C
+ Conductor	Iron

- Conductor	Constantan
Screen	No
Standards Met	Colour code (cores & jacket) to IEC-584-3
Thermocouple Type	J
Tolerance	Class 1