



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Termopar mineral aislado IEC con olla roscada y 100 mm de plomo IEC doble torcido aislado con PFA - Tipo K - 6,0 mm x 2000 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Necesitas calibrar tu sensor de temperatura?

Rastreable a estándares de calibración ISO17025 (UKAS), Labfacility ofrece la opción de calibración trazable en 3 o 5 puntos utilizando nuestra instalación de calibración interna.

Ten en cuenta que si añades una opción de calibración a tu pedido, te contactaremos para información de entrega.

Especificaciones

Specifications

| | |
|-----------------------------|--|
| Product Code | XE-3344-001 |
| General Description | Mineral insulated thermocouple in various lengths terminated with 100mm, PFA insulated twin twisted IEC. |
| Sensor Type | Mineral Insulated |
| Thermocouple Type | K |
| Element/hot junction | Single element, junction insulated from sheath (offers protection against spurious electrical signals) |
| Probe Diameter | 6.0mm |
| Probe Length | 2000mm |
| Sheath Material | 310 Stainless Steel |
| Pot Type | M8 x 1.0mm fine pitch threaded pot seal (200°C) |
| Cable Length | 100mm |
| Cable Type | PFA insulated twin twisted IEC |
| Core / Strands | 7/0.2mm |
| Termination Type | Bare Tails |



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

| | |
|-------------------------|-------------------|
| Max. Temperature | 1100°C |
| Min. Temperature | -40°C |
| Standards Met | IEC 584 |
| Series | Mineral Insulated |