



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Termopar Mineral Aislado IEC con Sello de Olla Lisa y 1 m de plomo IEC aislado con PFA - Tipo K - 1,0 mm x 150 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Necesitas calibrar tu sensor de temperatura?

Rastreable a estándares de calibración ISO17025 (UKAS), Labfacility ofrece la opción de calibración trazable en 3 o 5 puntos utilizando nuestra instalación de calibración interna.

Ten en cuenta que si añades una opción de calibración a tu pedido, te contactaremos para información de entrega.

Especificaciones

Specifications

Product Code	XE-3095-001
General Description	Plain pot seal (200°C) with 1 Metre of PFA insulated lead, 7/0.2mm flat pair with tails.
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	1.0mm
Probe Length	150mm
Sheath Material	310 Stainless Steel
Pot Type	Plain (+200°C)
Cable Length	1M
Cable Type	PFA Teflon® insulated flat pair cable and tails (colour coded to IEC 584)
Core / Strands	7/0.2mm
Termination Type	Bare Tails



Max. Temperature	750°C
Min. Temperature	-40°C
Tolerance	Class 1
Standards Met	In accordance with IEC 584
Series	Mineral Insulated