

Termopar Mineral Aislado IEC con tapn estndar - Tipo K - 3,0mm x 500mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Necesitas calibrar tu sensor de temperatura?

Rastreable a estándares de calibración ISO17025 (UKAS), Labfacility ofrece la opción de calibración trazable en 3 o 5 puntos utilizando nuestra instalación de calibración interna.

Ten en cuenta que si añades una opción de calibración a tu pedido, te contactaremos para información de entrega.

Especificaciones**Specifications**

Product Code	XE-3706-001
General Description	Highly flexible, sheath can be bent/formed to suit many applications and processes
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	3.0mm
Probe Length	500mm
Sheath Material	310 Stainless Steel
Termination Type	Standard round pin plug, colour coded in accordance IEC 584-3
Max. Temperature	1100°C
Min. Temperature	-40°C
Standards Met	In accordance with IEC 584-1&2
Connector Type	Plug
Connector Size	Standard



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Colour	Green
--------	-------