



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Termopar con aislamiento mineral ANSI con potencimetro roscado y 100 mm de cable ANSI trenzado doble aislado con PFA - Tipo K - Funda Inconel 600 - 3,0 mm x 2000 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Necesita calibrar su sensor de temperatura?

Trazable a ISO17025 estándares de calibración (UKAS), Labfacility ofrece una opción de calibración trazable de 3 o 5 puntos utilizando nuestra instalación de calibración interna.

Tenga en cuenta que si agrega una opción de calibración a su pedido, se comunicará con usted con respecto a la información de entrega.

Características técnicas**Specifications**

Product Code	XE-3046-001
General Description	Highly flexible, sheath can be bent/formed to suit many applications and processes
Thermocouple Type	K
Thermocouple Junction	Insulated hot junction
Probe Diameter	3.0mm
Probe Length	2000mm
Sheath Material	Inconel® Alloy 600 sheath
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA twin twisted
Core / Strands	7/0.2mm
Cable Termination	Bare tails
Max. Temperature	1100°C
Standards Met	colour coded to ANSI MC96.1