Termopar Mineral Aislado ANSI con Potencimetro Roscado y 100 mm de plomo ANSI doble torcido aislado con PFA - Tipo K - Vaina Inconel 600 - 3,0 mm x 3000 mm





Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Datasheet

Necesitas calibrar tu sensor de temperatura?

Rastreable a estndares de calibracin ISO17025 (UKAS), Labfacility ofrece la opcin de calibracin trazable en 3 o 5 puntos utilizando nuestra instalacin de calibracin interna.

Ten en cuenta que si aades una opcin de calibracin a tu pedido, te contactarn para informacin de entrega.

Especificaciones

Specifications

Product Code	XE-3047-001
General Description	Highly flexible, sheath can be bent/formed to suit many applications and processes
Thermocouple Type	K
Thermocouple Junction	Insulated hot junction
Probe Diameter	3.0mm
Probe Length	3000mm
Sheath Material	Inconel® Alloy 600 sheath
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA twin twisted
Core / Strands	7/0.2mm
Cable Termination	Bare tails
Max. Temperature	1100°C
Standards Met	colour coded to ANSI MC96.1
Series	Mineral Insulated