



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Detectores de resistencia de platino con cables extendidos, película delgada - Pt100 Clase A-4 hilos - Longitud de cable extendida de 1000 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Adecuado para aplicaciones de aire, superficie e inmersin (adecuado solo en atmósferas secas y no contaminantes donde no estn protegidas. Se requiere una proteccin/revestimiento adecuado para la inmersin en fluidos, sustancias corrosivas, procesos, etc.)

Características técnicas**Specifications**

Product Code	XE-5589-001
General Description	Platinum Resistance Detectors with extended leads, Thin Film
Sensor Type	Platinum Resistance, Pt100 Ohms
Element	Thin Film - Pt100 Ohm
Cable Length	1000mm
Cable Type	Teflon® insulated, stranded conductors
Core / Strands	7/0.15mm
Cable Termination	Bare tails
Max. Temperature	250°C
Min. Temperature	-50°C
Tolerance	Class A
Standards Met	European / British Standard Conforms to IEC 60751:2008 / BS EN 60751:2008
Extended lead wire configuration	4 Wire
Fundamental interval	(0°C to 100°C): 38.5 ohms nominal (100 ohms)
Ice point resistance	100 Ohms
Series	Extended Leads Pt100