

Termopar con aislamiento mineral con cabezal terminal KNS compacto - Tipo K - 6,0 mm de diametro - 100 mm de longitud



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Necesita calibrar su sensor de temperatura?

Trazable a los estándares de calibración ISO17025 (UKAS), Labfacility ofrece la opción de una calibración trazable de 3 o 5 puntos utilizando nuestra instalación de calibración interna, puede seleccionar cualquier punto de temperatura entre -10 C y +200 C.

Tenga en cuenta que si agrega una opción de calibración a su pedido, nos pondremos en contacto con usted con respecto a la información de entrega.

Características técnicas**Specifications**

Product Code	XE-3320-001
General Description	Flexible mineral insulated probe with 310 stainless steel sheath
Sensor Type	Type 'K' (Nickel Chromium/Nickel Aluminium) to IEC 584
Thermocouple Junction	Insulated hot junction
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	6.0mm
Probe Length	100mm
Sheath Material	310 stainless steel sheath
Head Type	KNS, Cast aluminium finish, screw type lid with chain. Head fitted 2-way ceramic block
Gland	M16 x 1.5mm Plated brass gland fitted
Max. Temperature	+1100°C (Max temp of head is 170°C)
Min. Temperature	-40°C
IP Rating	IP67



Series

Mineral Insulated