Kit de competicin econmico 1 con sonda fija para neumticos







Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Datasheet

Equipacin de competicin econmica 1

Incluye sonda fija para neumticos de competicin, medidor digital y maletn de transporte blando

Sonda de neumticos

Prueba fija de neumtico de competicin de respuesta rpida con una profundidad mxima de seis milmetros

Un rango de temperatura de -50 a +250C

Tipo de enlace - Conectado a tierra

Longitud de sonda de 6 mm, punta de 1,1 mm de dimetro

Equipado con cable enrollado de 1 m y tapn miniatura

Puede usarse con cualquier termmetro digital con un enchufe de entrada mini tipo K

Termmetro digital de uso general GM1312 (K,J,T,E,N,R/S)

modos K, J, T, E, N, R/S.

2 modos de temperatura: C, F

Un botn para cambiar entre el modo F/ C y tambin entre MAX/MIN/PROMEDIO.

2 canales de temperatura: T1 / T2

Medicin diferencial de temperatura

Alerta de pantalla de sobrecarga si la entrada excede el rango de medicin seleccionado

Viene con funda de goma que protege el medidor de impactos. Diseo porttil y compacto

Specifications

Product Code	XE-KITRACE1
General Description	Includes fixed racing tyre probe, digital meter and soft carry case
Sensor Type	Fixed racing tyre probe - Grounded Junction
Thermocouple Type	Type K fast response fixed racing tyre probe with a max depth of six millimetre
Probe Diameter	1.1mm
Probe Length	6mm
Cable Length	1m

Cable Type	Coiled lead
Cable Termination	Miniature Plug
Max. Temperature	+250°C
Min. Temperature	-50°C
Digital Thermometer	GM1312 General Purpose Digital Thermometer *K, J, T, E, N, R/S modes. *2 temperature modes: ° C, ° F *One push button to switch between ° F/° C mode as well to switch between MAX/MIN/AVG *2 temperature channels: T1 / T2 *Differential temperature measurement *Overload display alert if input exceeds the selected measurement range *Comes with rubber holster that protects the meter from impact Portable and compact design