Termopar con aislamiento mineral IEC con sello de olla liso, 1 m de cable IEC aislado con PFA y terminacin de mini enchufe - Tipo K - 4,5 mm x 500 mm

Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Datasheet

Necesita calibrar su sensor de temperatura?

Trazable a ISO17025 estndares de calibracin (UKAS), Labfacility ofrece una opcin de calibracin trazable de 3 o 5 puntos utilizando nuestra instalacin de calibracin interna.

Tenga en cuenta que si agrega una opcin de calibracin a su pedido, se comunicar con usted con respecto a la informacin de entrega.

Caractersticas tcnicas

Specifications

Product Code	XE-0335-001
General Description	Plain pot seal (200°C) with 1 Metre of PFA insulated lead, 7/0.2mm flat pair with tails.
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	4.5mm
Probe Length	500mm
Sheath Material	Stainless steel 310
Pot Type	Plain (+200°C)
Cable Length	1m
Cable Type	PFA Teflon® insulated flat pair cable and tails (colour coded to IEC 584)
Core / Strands	7/0.2mm
Termination Type	Fitted mini plug

Max. Temperature	+1100°C
Min. Temperature	-40°C
Tolerance	Class 1
Standards Met	In accordance with IEC 584
Connector Type	Plug
Connector Size	Miniature
Colour	Green