



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Termopar aislado con minerales ANSI de 0.5mm de diametro con potencimetro roscado ANSI y colas - Unin con conexin a tierra - Longitud de sonda de 50mm

50mm
0.5mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Tipo K con olla roscada y colas en acero inoxidable 310

Para 0.25mm, 0.75mm & 0.81mm de diametro y para versiones de funda de aleacin Inconel 600, por favor utilice nuestros

[formularios de sensores personalizados](#)

para enviar sus requisitos o enve un correo electronico sales@labfacility.com / telfono 01243 871280

Necesita calibrar su sensor de temperatura?

Trazable a los estndares de calibracin ISO17025 (UKAS), Labfacility ofrece una opcin de calibracin trazable de 3 o 5 puntos utilizando nuestra instalacin de calibracin interna, puede seleccionar cualquier punto de temperatura entre -10 C y + 200 C.

Tenga en cuenta que si agrega una opcin de calibracin a su pedido, se comunicar con usted con respecto a la informacin de entrega.

Caractersticas tcnicas

Specifications

Product Code	XE-0172-001
General Description	Type K with threaded pot & tails in 310 stainless steel
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction grounded from sheath
Probe Diameter	0.5mm
Probe Length	50mm
Sheath Material	310 stainless steel
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA insulated twin twisted ANSI
Core / Strands	7/0.2mm



Termination Type	Bare tails
Max. Temperature	+650°C
Min. Temperature	-40°C
Standards Met	In accordance with ANSI MC96.1
Connector Type	Plug
Connector Size	Miniature