

Termopar de respuesta rpida de 0,75 mm de dimetro con enchufe IEC en miniatura - Unin conectada a tierra - 150 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Tipo K Acero inoxidable 316 con aislamiento mineral, equipado con minitapn

Si requiere cantidades mayores, enve un correo electrnico sales@labfacility.com o llame a nuestra lnea de ventas 01243 871280.

Necesita calibrar su sensor de temperatura?

Trazable a los estndares de calibracin ISO17025 (UKAS), Labfacility ofrece la opcin de una calibracin trazable de 3 o 5 puntos utilizando nuestra instalacin de calibracin interna, puede seleccionar cualquier punto de temperatura entre -10 C y +200 C.

Tenga en cuenta que si agrega una opcin de calibracin a su pedido, nos pondremos en contacto con usted con respecto a la informacin de entrega.

Caractersticas tcnicas

Specifications

Product Code	XE-0186-001
General Description	Type K 316 stainless steel, Fitted with miniplug
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction grounded from sheath
Probe Diameter	0.75mm
Probe Length	150mm
Sheath Material	316 stainless steel
Pot Type	Plain (+200°C)
Cable Length	1M
Cable Type	PFA Teflon® insulated flat pair cable and tails (colour coded to IEC 584)(Max Temp 250°C)
Core / Strands	7/0.2mm



Termination Type	Thermocouple IEC Mini plug (Max Temp 200°C)
Max. Temperature	+750°C
Min. Temperature	-100°C
Tolerance	Class 1
Standards Met	In accordance with IEC 584