

0,75 mm de diametro Sello liso de olla con 1 metro de plomo aislado con PFA, par plano de 7/0,2 mm con colas ANSI - Unin aislada - 150 mm Longitud



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Sello de trampa liso con 1 metro de plomo aislado con PFA, par plano de 7/0,2 mm con cola.

Las sondas de termopar de unin de transicin de dimetro fino tienen la funda crimpada a un can de acero inoxidable sellado con epoxi y con un cable de derivacin aislado con PFA.

Si necesita cantidades mayores, por favor enva un correo electrnico a sales@labfacility.com o llame a nuestra lnea de ventas al 01243 871280.

Necesitas calibrar tu sensor de temperatura?

Rastreable a estndares de calibracin ISO17025 (UKAS), Labfacility ofrece la opcin de calibracin trazable en 3 o 5 puntos utilizando nuestra instalacin de calibracin interna.

Ten en cuenta que si aades una opcin de calibracin a tu pedido, te contactarn para informacin de entrega.

Caractersticas tcnicas

Specifications

Product Code	XE-0216-001
General Description	Plain pot seal (200°C) with 1 Metre of PFA insulated lead, 7/0.2mm flat pair with tails.
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated
Probe Diameter	0.75mm
Probe Length	150mm
Sheath Material	K - Stainless steel 316
Pot Type	Plain (+200°C)
Cable Length	1M



Cable Type	PFA Teflon® insulated flat pair cable and tails (colour coded to ANSI MC96.1)(Max Temp 250°C)
Core / Strands	7/0.2mm
Termination Type	Bare Tails
Max. Temperature	+750°C
Min. Temperature	-100°C
Tolerance	Class 1
Standards Met	In accordance with ANSI MC96.1