

**Termopar mineral aislado de 0,75 mm de diametro
con tapn ANSI miniatura Unin aislada - longitud
de sonda de 250 mm**



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Acero inoxidable tipo K Mineral Mineral Aislado 316, equipado con miniplug

Si necesita cantidades mayores, por favor envíe un correo electrónico a sales@labfacility.com o llame a nuestra línea de ventas al 01243 871280.

Necesitas calibrar tu sensor de temperatura?

Rastreable a estándares de calibración ISO17025 (UKAS), Labfacility ofrece la opción de calibración trazable en 3 o 5 puntos utilizando nuestra instalación de calibración interna.

Ten en cuenta que si añades una opción de calibración a tu pedido, te contactaremos para información de entrega.

Características técnicas

Specifications

Product Code	XE-0220-001
General Description	Type K 316 stainless steel, Fitted with miniplug
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath
Probe Diameter	0.75mm
Probe Length	250mm
Sheath Material	316 stainless steel
Pot Type	Thermocouple ANSI Mini plug (Max Temp 200°C)
Termination Type	Miniature Plug
Max. Temperature	+750°C
Min. Temperature	-100°C
Tolerance	Class 1



Standards Met	In accordance with ANSI MC96.1
Connector Type	Plug
Connector Size	Miniature
Colour	Yellow