



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

**Termopar IEC de respuesta rpida de 0,81 mm de
dimetro Sello de olla lisa con 1 metro de cable
aislado PFA, par plano de 7/0,2 mm con colas -
Unin aislada - 150 mm**



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Si requiere cantidades mayores, envíe un correo electrónico sales@labfacility.com o llame a nuestra línea de ventas 01243 871280.

Necesita calibrar su sensor de temperatura?

Trazable a los estándares de calibración ISO17025 (UKAS), Labfacility ofrece la opción de una calibración trazable de 3 o 5 puntos utilizando nuestras instalaciones de calibración internas.

Tenga en cuenta que si agrega una opción de calibración a su pedido, nos pondremos en contacto con usted con respecto a la información de entrega. .

Características técnicas

Specifications

Product Code	XE-0237-001
General Description	Plain pot seal (200°C) with 1 Metre of PFA insulated lead, 7/0.2mm flat pair with tails.
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath
Probe Diameter	0.81mm
Probe Length	150mm
Sheath Material	K - Stainless steel 316
Pot Type	Plain (+200°C)
Cable Length	1M
Cable Type	PFA Teflon® insulated flat pair cable and tails (colour coded to IEC 584) (Max Temp 250°C)
Core / Strands	7/0.2mm



Termination Type	Bare Tails
Max. Temperature	K +650°C
Min. Temperature	K -40°C
Tolerance	Class 1
Standards Met	In accordance with IEC 584