



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Termopar de respuesta rpida de 0,81 mm de dimetro con olla y colas roscadas IEC - Unin aislada - 150 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Si requiere cantidades mayores, envíe un correo electrónico sales@labfacility.com o llame a nuestra línea de ventas 01243 871280.

Necesita calibrar su sensor de temperatura?

Trazable a los estándares de calibración ISO17025 (UKAS), Labfacility ofrece la opción de una calibración trazable de 3 o 5 puntos utilizando nuestras instalaciones de calibración internas.

Tenga en cuenta que si agrega una opción de calibración a su pedido, nos pondremos en contacto con usted con respecto a la información de entrega. .

Características técnicas

Specifications

Product Code	XE-0243-001
General Description	Type K with threaded pot & tails in 316 stainless steel
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath
Probe Diameter	0.81mm
Probe Length	150mm
Sheath Material	316 stainless steel
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA insulated twin twisted IEC (Temp -75 TO +250°C)
Core / Strands	7/0.2mm
Gland	Bare Tails
Max. Temperature	+650°C



Min. Temperature	-40°C
Tolerance	Class 1
Standards Met	In accordance with IEC 584