



# LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

## **Termopar magnético de potencia de tracción (herradura) tipo K ANSI, cable aislado con PFA con terminación de trenzado de acero inoxidable en enchufe estándar - 1M**



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

**Características técnicas****Specifications**

|                            |   |
|----------------------------|---|
| <b>Product Code</b>        | XE-0668-001   |
| <b>General Description</b> | 4.5kg Pull Power (Horseshoe) Magnet Thermocouple      |
| <b>Sensor Type</b>         | Magnet Thermocouple                                   |
| <b>Thermocouple Type</b>   | K   |
| <b>Magnet</b>              | 30 x 20 x 20mm (L x H x W). Max Pull: 4.5kg           |
| <b>Cable Length</b>        | 1M  |
| <b>Cable Type</b>          | PFA Teflon® insulated with stainless steel over-braid |
| <b>Core / Strands</b>      | 7/0.2mm   |
| <b>Termination Type</b>    | Standard Plug   |
| <b>Max. Temperature</b>    | 250°C   |
| <b>Min. Temperature</b>    | -50°C   |
| <b>Standards Met</b>       | ANSI MC96.1   |
| <b>Series</b>              | Magnet Thermocouple                                   |