




LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Termopar mineral aislado JIS con potencimetro roscado y 100 mm de plomo JIS gemelo torcido aislado con PFA - Tipo K - 1,5 mm x 250 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Necesitas calibrar tu sensor de temperatura?

Rastreable a estándares de calibración ISO17025 (UKAS), Labfacility ofrece la opción de calibración trazable en 3 o 5 puntos utilizando nuestra instalación de calibración interna.

Ten en cuenta que si añades una opción de calibración a tu pedido, te contactaremos para información de entrega.

Especificaciones

Specifications

Product Code	XE-2926-001
General Description	Mineral insulated thermocouple in various lengths terminated with 100mm, PFA insulated twin twisted IEC.
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	1.5mm
Probe Length	250mm
Sheath Material	310 Stainless Steel
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA insulated twin twisted JIS
Core / Strands	7/0.2mm
Termination Type	Bare Tails



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Max. Temperature	1100°C
Min. Temperature	-40°C
Standards Met	JIS
Series	Mineral Insulated